



FORD PERFORMANCE

M-6010-16K 1.6 LITER 4-CYLINDER KENT ENGINE BLOCK

NO PART OF THIS DOCUMENT MAY BE REPRODUCED WITHOUT PRIOR AGREEMENT AND WRITTEN PERMISSION OF
FORD PERFORMANCE PARTS © Ford Motor Company 2020

PRIOR TO INSTALLATION READ THESE INSTRUCTION COMPETELY
For questions, Call the FORD PERFORMANCE Techline 1-800-367-3788

Please visit <https://www.performanceparts.ford.com> for warranty information

OVERVIEW:

This sheet contains important information regarding dimensions and specifications of the M-6010-16K blocks. These instructions should be reviewed by all engine builders, due to minor changes that could impact the engine assembly process.

CONTENTS:

Be sure to check for the following parts included with M-6010-16K.

- (1) 2.070" cup plug
- (2) 1.625" cup plugs
- (5) 1/4-18 npt pipe plugs
- Cam bearings installed (3C711S ACL bearing set)
- (1)1/8-27 npt pipe plug
- (2) Clutch housing dowels

FEATURES AND SPECIFICATIONS:

Part Number	M-6010-16K
Material	Cast iron
Bore Size	M-6010-16K 3.185"-3.187"
Bore Spacing	3.780"
Block Deck Height (out of box)	8.328"
Head Bolt Size	7/16-14 UNC Head bolts
Main Bolt configuration	2 bolt main caps 7/16-14 UNC
Main Bearing Bore Size	2.2702" – 2.2710"
Main Cap Material	Nodular cast iron main caps
Main Cap Fasteners	7/16-14 UNC (torque spec. 70 lb-ft) ARP recommended torque value
Cam Bearing Bore Size	1.6895" - 1.6905"
Cam Bearing I.D.	1.5615" – 1.5620"
Lifter Bore Size	.5160" - .5170"
Oiling System	Wet sump oiling system
Rear Seal Type	Rear engine cover mounted 1 piece rear seal

Recommended Parts

Valve cover M-6582-16K Cast Kent rocker cover

Ford Factory Shop Manual purchase options www.motorcraftservice.com